

C++ POINTER ARITHMETIC

https://www.tutorialspoint.com/cplusplus/cpp_pointer_arithmetic.htm

Copyright © tutorialspoint.com

Advertisements

As you understood pointer is an address which is a numeric value; therefore, you can perform arithmetic operations on a pointer just as you can a numeric value. There are four arithmetic operators that can be used on pointers: ++, --, +, and -

To understand pointer arithmetic, let us consider that **ptr** is an integer pointer which points to the address 1000. Assuming 32-bit integers, let us perform the following arithmetic operation on the pointer –

```
ptr++
```

the **ptr** will point to the location 1004 because each time ptr is incremented, it will point to the next integer. This operation will move the pointer to next memory location without impacting actual value at the memory location. If ptr points to a character whose address is 1000, then above operation will point to the location 1001 because next character will be available at 1001.

Incrementing a Pointer

We prefer using a pointer in our program instead of an array because the variable pointer can be incremented, unlike the array name which cannot be incremented because it is a constant pointer. The following program increments the variable pointer to access each succeeding element of the array –

[Live Demo](#)

```
#include <iostream>

using namespace std;
const int MAX = 3;

int main () {
    int var[MAX] = {10, 100, 200};
    int *ptr;

    // Let us have array address in pointer.
    ptr = var;

    for (int i = 0; i < MAX; i++) {
        cout << "Address of var[" << i << "] = ";
        cout << ptr << endl;

        cout << "Value of var[" << i << "] = ";
        cout << *ptr << endl;

        // point to the next location
        ptr++;
    }

    return 0;
}
```

When the above code is compiled and executed, it produces result something as follows –

```
Address of var[0] = 0xbfa088b0
Value of var[0] = 10
Address of var[1] = 0xbfa088b4
```

```
Value of var[1] = 100
Address of var[2] = 0xbfa088b8
Value of var[2] = 200
```

Decrementing a Pointer

The same considerations apply to decrementing a pointer, which decreases its value by the number of bytes of its data type as shown below –

[Live Demo](#)

```
#include <iostream>

using namespace std;
const int MAX = 3;

int main () {
    int var[MAX] = {10, 100, 200};
    int *ptr;

    // Let us have address of the last element in pointer.
    ptr = &var[MAX-1];

    for (int i = MAX; i > 0; i--) {
        cout << "Address of var[" << i << "] = ";
        cout << ptr << endl;

        cout << "Value of var[" << i << "] = ";
        cout << *ptr << endl;

        // point to the previous location
        ptr--;
    }

    return 0;
}
```

When the above code is compiled and executed, it produces result something as follows –

```
Address of var[3] = 0xbfdb70f8
Value of var[3] = 200
Address of var[2] = 0xbfdb70f4
Value of var[2] = 100
Address of var[1] = 0xbfdb70f0
Value of var[1] = 10
```

Pointer Comparisons

Pointers may be compared by using relational operators, such as ==, <, and >. If p1 and p2 point to variables that are related to each other, such as elements of the same array, then p1 and p2 can be meaningfully compared.

The following program modifies the previous example one by incrementing the variable pointer so long as the address to which it points is either less than or equal to the address of the last element of the array, which is &var[MAX - 1] –

[Live Demo](#)

```
#include <iostream>
```

```
using namespace std;
const int MAX = 3;

int main () {
    int var[MAX] = {10, 100, 200};
    int *ptr;

    // let us have address of the first element in pointer.
    ptr = var;
    int i = 0;

    while ( ptr <= &var[MAX - 1] ) {
        cout << "Address of var[" << i << "] = ";
        cout << ptr << endl;

        cout << "Value of var[" << i << "] = ";
        cout << *ptr << endl;

        // point to the previous location
        ptr++;
        i++;
    }

    return 0;
}
```

When the above code is compiled and executed, it produces result something as follows –

```
Address of var[0] = 0xbfce42d0
Value of var[0] = 10
Address of var[1] = 0xbfce42d4
Value of var[1] = 100
Address of var[2] = 0xbfce42d8
Value of var[2] = 200
```